

SDS ID No.: AM USA - 006

Safety Data Sheet (SDS)

Section 1 – Identification

1(a) Product Identifier used on Label: Tin Mill Products

1(b) Other means of identification: Refer to Section 16 for product synonyms.

1(c) Recommended use of the chemical and restrictions on use: These products are sold to all steel-consuming industries including automotive, heavy machinery, pipes and tubes, construction, packaging and appliances. The main markets for these products are construction and mechanical engineering, as well as energy and automotive applications.

1(d) Name, address, and telephone number:

ArcelorMittal USA LLC Phone number: 219-787-4901 or 1 South Dearborn Street email at: msdssupport@arcelormittal.com

Chicago, IL 60603-9888

1(e) Emergency phone number: 1-760-476-3962 (3E Company Code: 333211) or CHEMTREC (Day or Night): 1-800-424-9300

Section 2 – Hazard(s) Identification

2(a) Classification of the chemical: Tin Mill Products is considered an article under Reach regulation (REACH REGULATION (EC) No 1907/2006) and is not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008). However, Tin Mill Products is not exempt as an article under OSHA's Hazard Communication Standard (29 CFR 1910.1200) due to its downstream use, thus this product is considered a mixture and a hazardous material. Therefore, the categories of Health Hazards as defined in "GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3" United Nations, New York and Geneva, 2009 have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal word, hazard statement(s), symbols and precautionary statement(s):

Hazard Symbol	Hazard Classification	Signal Word	Hazard Statement(s)
	Carcinogenicity - 2 Reproductive Toxicity - 2 Single Target Organ Toxicity (STOT) Repeat Exposure - 1	Danger	Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to lungs and central nervous system through prolonged or
(1)	Skin Sensitization - 1 STOT Single Exposure - 3		repeated inhalation exposure. May cause an allergic skin reaction. May cause respiratory irritation. Causes eye irritation.
NA	Eye Irritation-2B		233222 2,7 11111110111

Precautionary Statement(s):

recutionary butterness(b).						
Prevention	Response	Storage/Disposal				
Do not breathe dusts / fume / gas / mist / vapor / spray.	If inhaled: Remove person to fresh air and keep comfortable					
Wear protective gloves / protective clothing / eye protection /	for breathing.					
face protection.	If exposed, concerned or feel unwell: Get medical					
Contaminated work clothing must not be allowed out of the	advice/attention.					
workplace.	If in eyes: Rinse cautiously with water for several minutes.	Dispose of contents in				
Use only outdoors or in well ventilated areas.	Remove contact lenses, if present and easy to do. Continue	accordance with federal, state				
Wash thoroughly after handling.	Rinsing.	and local regulations.				
Obtain special instructions before use.	If on skin: Wash with plenty of water. If irritation or rash					
Do not handle until all safety precautions have been read and	occurs: Get medical advice/attention. Take off and wash					
understood.	contaminated clothing before reuse.					
Do not eat, drink or smoke when using this product.	Call a poison center/doctor if you feel unwell.					

2(c) Hazards not otherwise classified: None Known

2(d) Unknown acute toxicity statement (mixture): None Known

Section 3 – Composition/Information on Ingredients

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration:

Chemical Name	CAS Number EC Number		% weight	
Iron	7439-89-6	231-096-4	>95 – 98	
Carbon	7440-44-0	231-153-3	0.001-1.10	
Manganese	7439-96-5	231-105-1	0-1.95	

SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 3 – Composition/Information on Ingredients (continued)

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration (continued):

Chemical Name	CAS Number	EC Number	% weight
Nickel	7440-02-0	231-111-4	0.01 - 0.15
Silicon	7440-21-3	231-130-8	0-1.45

EC - European Community

CAS - Chemical Abstract Service

All commercial steel products contain small amounts of various elements in addition to those listed. These small quantities are frequently referred to as "trace" or "residual" elements that generally originate in the raw materials used. Steel products may contain the following trace or residual elements including typical percentages for the elements identified: aluminum (0.05%), boron (≤0.005 max, typically 0.001%), calcium (≤ 0.005 max, typically 0.003%), chromium (0.01-0.1), columbium (≤0.15 max, typically 0.002%), copper (0-0.02), molybdenum (≤0.4 max, typically 0.006%), phosphorous (≤0.1 max, typically 0.01%), sulfur (≤0.05 max, typically 0.007%), tin (≤0.03 max, typically 0.002%), itianium (≤0.15 max, typically 0.002%), and vanadium (≤0.15 max, typically 0.001%). Other trace elements not frequently identified, may include antimony, arsenic, cadmium, cobalt, lead, and

Metallic Coating (if applicable) 1

*** * * * * * * * * * * * * * * * * *							
Chemical Name	CAS Number	EC Number	% weight ²				
Chromium	7440-47-3	231-157-5	0-94.9				
Chromium Oxide	1308-38-9	215-160-9	0 – 45.5				
Tin (Sn)	7440-31-5	231-141-8	0 ->99.85				

- 1. Refer to product specifications for coating applicability.
- 2. Percentages are expressed as typical ranges or maximum concentrations of elements in the coating, for the purpose of communicating the potential hazards of the finished product. Consult product specifications for specific composition information.

Section 4 – First-aid Measures

4(a) Description of necessary measures:

- Inhalation: Tin Mill Products as sold/shipped is not a likely form of exposure. However during further processing (welding, grinding, burning, etc.), if inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed, concerned or feel unwell: Get medical advice/attention.
- Eye Contact: Tin Mill Products as sold/shipped is not a likely form of exposure. However during further processing (welding, grinding, burning, etc.), if in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. If eye irritation persists: Get medical advice attention. If exposed, concerned or feel unwell: Get medical advice/attention.
- Skin Contact: If on skin: Wash thoroughly after handling. Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash contaminated clothing before reuse. If exposed, concerned or feel unwell: Get medical advice/attention.
- Ingestion: Tin Mill Products as sold/shipped is not a likely form of exposure. However during further processing (welding, grinding, burning, etc.), if exposed, concerned or feel unwell: Get medical advice/attention.

4(b) Most important symptoms/effects, acute and delayed (chronic):

- Inhalation: Tin Mill Products as sold/shipped is not likely to present an acute or chronic health effect.
- Eye: Tin Mill Products as sold/shipped is not likely to present an acute or chronic health effect.
- Skin: Tin Mill Products as sold/shipped is not likely to present an acute or chronic health effect.
- Ingestion: Tin Mill Products as sold/shipped is not likely to present an acute or chronic health effect.

However during further processing (welding, grinding, burning, etc.) individual components may illicit an acute or chronic health effect. Refer to Section 11-Toxicological Information.

4(c) Immediate Medical Attention and Special Treatment: None Known

Section 5 – Fire-fighting Measures

- **5(a) Suitable (and unsuitable) Extinguishing Media:** Not Applicable for **Tin Mill Products** as sold/shipped. Use extinguishers appropriate for surrounding materials.
- **5(b) Specific Hazards arising from the chemical:** Not Applicable for **Tin Mill Products** as sold/shipped. When burned, toxic smoke, fume and vapor may be emitted.
- **5(c) Special protective equipment and precautions for fire-fighters:** Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

- **6(a) Personal Precautions, Protective Equipment and Emergency Procedures:** Not Applicable for **Tin Mill Products** as sold/shipped. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust.
- **6(b) Methods and materials for containment and clean up:** Not Applicable for **Tin Mill Products** as sold/shipped. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 7 - Handling and Storage

7(a) **Precautions for safe handling:** Not Applicable for **Tin Mill Products** as sold/shipped, however further processing (welding, burning, grinding, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in well ventilated areas. Practice good housekeeping. Avoid breathing metal fumes and/or dust. Do not eat, drink or smoke when using this product. Cut resistant gloves and sleeves should be worn when working with steel products.

7(b) Conditions for safe storage, including any incompatibilities: Store away from acids and incompatible materials.

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): Tin Mill Products as sold/shipped in its physical form does not present an inhalation, ingestion or contact hazard, nor would any of the following exposure data apply. However, operations such as burning, welding (high temperature), sawing, brazing, machining, grinding, etc. may produce fumes and/or particulates. The following exposure limits are offered as reference for an experienced industrial hygienist to review.

Ingredients	OSHA PEL ¹	ACGIH TLV ²	NIOSH REL ³	IDLH ⁴
Iron	10 mg/m³ (as iron oxide fume)	5.0 mg/m³ (as iron oxide dust and fume)	5.0 mg/m³ (as iron oxide dust and fume)	2,500 mg Fe/m ³
Carbon	15 mg/m³ (as total dust, PNOR5)	10 mg/m³ (as inhalable fraction, ⁶ PNOS ⁷)	NE	NE
	5.0 mg/m³ (as respirable fraction, PNOR)	3.0 mg/m³ (as respirable fraction, PNOS)		
Manganese	(C) 5.0 mg/m³ (as Fume & Mn	0.2 mg/m ³	(C) 5.0 mg/m^3	500 mg Mn/m^3
	compounds)		1.0 mg/m³ (as fume)	
			(STEL) 3.0 mg/m ³	
Nickel	1.0 mg/m³ (as Ni metal & insoluble compounds)	1.5 mg/m³ (as inhalable fraction Ni metal)	0.015 mg/m³ (as Ni metal & insoluble and soluble	10 mg/m³ (as Ni)
		0.2 mg/m³ (as inhalable fraction Ni inorganic only insoluble and soluble compounds)	compounds)	
Silicon	15 mg/m³ (total dust, PNOR)	10 mg/m³	10 mg/m³ (as total dust)	NE
	5.0 mg/m³ (as respirable fraction, PNOR)		5.0 mg/m³ (as respirable dust)	
Chromium	0.5 mg/m³ (as Cr II & III, inorganic compounds)	0.5 mg/m³ (as Cr III, inorganic compounds)	0.5 mg/m³ (as Cr II & III, inorganic compounds)	250 mg/m³ (as Cr II & metal)
	1.0 mg/m³ (as Cr, metal)	0.5 mg/m³ (as Cr, metal)	0.5 mg/m³ (as Cr, metal)	25 mg/m³ (as Cr III)
	0.005 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	0.05 mg/m³ (as Cr VI, inorganic compounds)	0.001 mg/m³ (as Cr VI, inorganic compounds &	15 mg/m³ (as Cr VI)
	"AL" 0.0025 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	0.01 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	certain water insoluble)	
Tin	2.0 mg/m³ (as inorganic compounds, Sn)	2.0 mg/m³ (as metal and inorganic compounds, Sn)	2.0 mg/m³ (also applies to other inorganic tin compounds, as Sn except tin oxides)	100 mg/m ³ (as Sn)

NE - None Established

- 1. OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (C) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Peak is defined as the acceptable maximum peak for a maximum duration above the ceiling concentration for an eight-hour shift. A skin notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
- 2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures. A "skin" notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. ACGIH-TLVs are only recommended guidelines based upon consensus agreement of the membership of the ACGIH. As such, the ACGIH TLVs are for guideline use purposes and are not legal regulatory standards for compliance purposes. The TLVs are designed for use by individuals trained in the discipline of industrial hygiene relative to the evaluation of exposure to various chemical or biological substances and physical agents that may be found in the workplace.
- 3. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL)- Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
- 4. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994.
- 5. PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by a limit which is the same as the inert or nuisance dust limit of 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction.
- 6. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2015 TLVs * and BEIs * (Biological Exposure Indices) Appendix D, paragraph A.
- 7. PNOS (Particulates Not Otherwise Specified). Particulates identified under the PNOS heading are "nuisance dusts" containing no asbestos and <1% crystalline silica.
- 8. Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in ACGIH 2015 TLVs ** and BEIs ** Appendix D, paragraph C.

SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 8 - Exposure Controls / Personal Protection (continued)

8(c) Individual Protection Measures:

• Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (Immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure, and powered-air do not protect workers in oxygen-deficient atmospheres.

- Eyes: Wear appropriate eye protection to prevent eye contact. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material are likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.
- Skin: Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations. Contaminated work clothing must not be allowed out of the workplace.
- Other protective equipment: An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties

9(a) Appearance (physical state, color, etc.): Solid, Metallic Gray

9(b) Odor: Odorless 9(c) Odor Threshold: NA

9(d) pH: NA

9(e) Melting Point/Freezing Point: ~2750 °F (~1510 °C) 9(f) Initial Boiling Point and Boiling Range: ND

9(g) Flash Point: NA 9(h) Evaporation Rate: NA

9(i) Flammability (solid, gas): Non-flammable, non-combustible

NA - Not Applicable

 $\mathbf{N}\mathbf{D}$ - Not Determined for product as a whole

9(j) Upper/lower Flammability or Explosive Limits: NA

9(k) Vapor Pressure: NA 9(l) Vapor Density (Air = 1): NA 9(m) Relative Density: 7.85 9(n) Solubility(ies): Insoluble

9(o) Partition Coefficient n-octanol/water: ND

9(p) Auto-ignition Temperature: NA **9(q) Decomposition Temperature**: ND

9(r) Viscosity: NA

Section 10 - Stability and Reactivity

10(a) Reactivity: Not Determined (ND) for product in a solid form. Do not use water on molten metal.

10(b) Chemical Stability: Steel products are stable under normal storage and handling conditions.

10(c) Possibility of hazardous reaction: None Known

10(d) Conditions to Avoid: Storage with strong acids or calcium hypochlorite.

10(e) Incompatible Materials: Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.

10(f) Hazardous Decomposition Products: Thermal oxidative decomposition of steel products can produce fumes containing oxides of iron and manganese as well as other alloying elements.

Section 11 - Toxicological Information

11 Information on toxicological effects: The following toxicity data has been determined for **Tin Mill Products** when further processed using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL:

Hazard Classification	Hazard Category Haza		Hazard	Signal Word	Hazard Statement	
mazaru Ciassification	EU	OSHA	Symbols Signar Word			
Eye Damage/ Irritation (covers Categories 1, 2A and 2B)	NA*	2B ^c	No Pictogram	Warning	Causes eye irritation - Rating due to iron particulate generated from further processing (welding, grinding, burning, etc.).	
Skin/Dermal Sensitization (covers Category 1)	NA*	1 ^d	(1)	Warning	May cause an allergic skin reaction - Nickel is a skin sensitizer.	

SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 11 - Toxicological Information

11 Information on toxicological effects (continued):

11 Information on toxicological effects (continued):							
Hazard Classification	Hazard Category EU OSHA		Hazard Symbols	Signal Word	Hazard Statement		
Carcinogenicity (covers Categories 1A, 1B and 2)	NA*	2 ^g	\$	Warning	Suspected of causing cancer Rating due to nickel particulate or fume that can enter the body generated when further processed (welding, grinding, burning, etc.).		
Toxic Reproduction (covers Categories 1A, 1B and 2)	NA*	2 ^h		Warning	Suspected of damaging fertility or the unborn child Rating due to nickel particulate or fume that can enter the body generated when further processed (welding, grinding, burning, etc.).		
Specific Target Organ Toxicity (STOT) Following Single Exposure (covers Categories 1-3)	NA*	3 ⁱ	Warning		May cause respiratory irritation Rating due to iron particulate or fume that can enter the body generated when further processed (welding, grinding, burning, etc.).		
STOT following Repeated Exposure (covers Categories 1 and 2)	NA*	1 ^j	\$	Danger	Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure Rating due to nickel or manganese particulate or fume that can enter the body generated when further processed (welding, grinding, burning, etc.).		

^{*} Not Applicable - Semi-formed steel products are considered articles under Reach regulation (REACH REGULATION (EC) No 1907/2006) and are not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008).

Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

- a. No LC₅₀ or LD₅₀ has been established for **Stainless Steel**. The following data has been determined for the components:
 - **Iron:** Rat LD₅₀ =98.6 g/kg (REACH)

Rat $LD_{50} = 1060 \text{ mg/kg (IUCLID)}$

Rat $LD_{50} = 984 \text{ mg/kg (IUCLID)}$

Rabbit LD₅₀ =890 mg/kg (IUCLID)

Guinea Pig LD₅₀ =20 g/kg (TOXNET)

• Nickel: $LD_{50} > 9000 \text{ mg/kg (Oral/Rat)}$

• Carbon: LD₅₀= >10,000 mg/kg (Oral/ Rat)

• Manganese: Rat LD₅₀ > 2000 mg/kg (REACH)

Rat $LD_{50} > 9000 \text{ mg/kg}$ (NLM Toxnet)

• Silicon: $L_{D50} = 3160 \text{ mg/kg (Oral/Rat)}$

- b. No Skin (Dermal) Irritation data available for Tin Mill Products as a as a mixture or it's components.
- c. No Eye Irritation data available for **Tin Mill Products** as a mixture. The following Eye Irritation information was found for the components:
 - Iron: Causes eye irritation.
 - Nickel: Slight eye irritation from particulate abrasion only.
 - Silicon: Slight eye irritation in rabbit protocol.
- d. No Skin (Dermal) Sensitization data available for Tin Mill Products as a mixture. The following Skin (Dermal) Sensitization information was found for the components:
 - Nickel: May cause allergic skin sensitization.
- e. No Respiratory Sensitization data available for Tin Mill Products as a mixture or its components.
- f. No Germ Cell Mutagenicity data available for **Tin Mill Products** as a mixture. The following Mutagenicity and Genotoxicity information was found for the components:
 - Iron: IUCLID has found some positive and negative findings in vitro.
 - Nickel: EU RAR has found positive results in vitro and in vivo but insufficient data for classification.
- g. Carcinogenicity: IARC, NTP, and OSHA do not list **Tin Mill Products** as carcinogens. The following Carcinogenicity information was found for the components:
 - Welding Fumes IARC Group 2B carcinogen, a mixture that is possibly carcinogenic to humans.
 - Chromium (as metal and trivalent chromium compounds) IARC Group 3 carcinogens, not classifiable as to their human carcinogenicity.
 - Nickel and certain nickel compounds Group 2B metallic nickel Group 1 nickel compounds ACGIH confirmed human carcinogen. Nickel –
 EURAR Insufficient evidence to conclude carcinogenic potential in animals or humans; suspect carcinogen classification Category 2 Suspected of
 causing cancer.
- h. No Toxic Reproduction data available for **Tin Mill Products** as a mixture. The following Toxic Reproductive information was found for the components:
 - · Nickel: Effects on fertility.
- i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Tin Mill Products** as a mixture. The following STOT following a Single Exposure data was found for the components:
 - Iron: Irritating to Respiratory tract.
- j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Tin Mill Products** as a whole. The following STOT following Repeated Exposure data was found for the components:
 - Nickel: Rat 4 wk inhalation LOEL 4 mg/m³ Lung and Lymph node histopathology. Rat 2 yr inhalation LOEL 0.1 mg/m³ Pigment in kidney, effects on hematopoiesis spleen and bone marrow and adrenal tumor. Rat 13 Week Inhalation LOAEC 1.0 mg/m³ Lung weights, and Alveolar histopathology.
 - Manganese: Inhalation of metal fumes Degenerative changes in human Brain; Behavioral: Changes in motor activity and muscle weakness (Whitlock et al., 1966).

Tin Mill Products

ArcelorMittal

SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 11 - Toxicological Information (continued)

11 Information on toxicological effects (continued):

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2009, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Packaging. (EU CPL), Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), International Uniform Chemical Information Database (IUCLID), TOXicology Data NETwork (TOXNET), European Risk Assessment Reports (EU RAR).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s) and potential resultant components from further processing:

Acute Effects:

- Inhalation: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Excessive inhalation of fumes of freshly formed metal oxide particles sized below 1.5 micrometer and usually between 0.02-0.05 micrometers from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms), metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. The symptoms come on in a few hours after excessive exposures and usually last from 12 to 48 hours. Long-term effects from metal fume fever have not been noted. Freshly formed oxide fumes of manganese and copper have been associated with causing metal fume fever.
- Eye: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes.
- Skin: Skin contact with metal dusts may cause irritation or sensitization, possibly leading to dermatitis. Skin contact with metallic fumes and dusts may cause physical abrasion.
- Ingestion: Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of metal dust may cause nausea or vomiting.

Acute Effects by component:

- Iron and iron oxides: Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.
- Carbon: Not Reported/ Not Classified
- Manganese and manganese oxides: Manganese and Manganese oxide are harmful if swallowed.
- Nickel and nickel oxides: Nickel may cause allergic skin sensitization. Nickel oxide may cause an allergic skin.
- Silicon and silicon oxides: May be harmful if swallowed.
- Chromium, chromium oxides and hexavalent chrome: Hexavalent chrome causes damage to gastrointestinal tract, lung, severe skin burns and eye damage, serious eye damage, skin contact may cause an allergic skin reaction. Inhalation may cause allergic or asthmatic symptoms or breathing difficulties.
- Tin: Not Reported/ Not Classified

Delayed (chronic) Effects by component:

- Iron and iron oxides: Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by the International Agency for Research on Cancer (IARC).
- Carbon: Chronic inhalation may lead to decreased pulmonary function.
- Manganese and manganese oxides: Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system with symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis. Animal studies indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure (Manganese) is a progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include altered gait, fine tremor, and sometimes, psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure. Neurobehavioral alterations in worker populations exposed to manganese oxides include: speed and coordination of motor function are especially impaired.
- Nickel and nickel oxides: Exposure to nickel dusts and fumes can cause sensitization dermatitis, respiratory irritation, asthma, pulmonary fibrosis, edema, and may cause nasal or lung cancer in humans. Nickel causes damage to lungs through prolonged or repeated inhalation exposure. IARC lists nickel and certain nickel compounds as Group 2B carcinogens (sufficient animal data). ACGIH 2013 TLVs® and BEIs® lists insoluble nickel compounds as confirmed human carcinogens. Nickel is suspected of damaging the unborn child.
- Silicon and silicon oxides: Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust. Eye contact with pure material can cause particulate irritation. Skin contact with silicon dusts may cause physical abrasion.
- Chromium, chromium oxides and hexavalent chromium: The health hazards associated with exposure to chromium are dependent upon its oxidation state. The metal form (chromium as it exists in this product) is of very low toxicity. The hexavalent form is very toxic. Repeated or prolonged exposure to hexavalent chromium compounds may cause respiratory irritation, nosebleed, ulceration and perforation of the nasal septum. Industrial exposure to certain forms of hexavalent chromium has been related to an increased incidence of cancer. NTP (The National Toxicology Program) Fourth Annual report on Carcinogens cites "certain Chromium compounds" as human carcinogens. ACGIH has reviewed the toxicity data and concluded that chromium metal is not classifiable as a human carcinogen. Hexavalent chromium may cause genetic defects and is suspected of damaging the unborn child. Developmental toxicity in the mouse, suspected of damaging fertility or the unborn child.
- Tin: No systemic effects have been reported from industrial exposure to tin. Occupational exposures to tin can cause a benign pneumoconiosis termed 'stannosis'. No cases of massive fibrosis from over-exposure to tin have been reported.

Tin Mill Products

Arcelor Mittal

SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No Data Available for Tin Mill Products as sold/shipped. However, individual components of the product when processed have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- Iron Oxide: LC₅₀: >1000 mg/L; Fish 48 h-EC₅₀ > 100 mg/L (Currenta, 2008k); 96 h-LC₀ ≥ 50,000 mg/L Test substance: Bayferrox 130 red (95 $97\% \text{ Fe}_2\text{O}_3$; $< 4\% \text{ SiO}_2$ and Al_2O_3) (Bayer, 1989a).
- Hexavalent Chrome: EU RAR listed as category 1, found acute EC₅₀ and LD₅₀ to algae and invertebrates < 1 mg.
- Nickel Oxide: IUCLID found LC₅₀ in fish, invertebrates and algae > 100 mg/l.
- 12(b) Persistence & Degradability: No Data Available for Tin Mill Products as sold/shipped or individual components.
- 12(c) Bioaccumulative Potential: No Data Available for Tin Mill Products as sold/shipped or individual components.
- 12(d) Mobility (in soil): No data available for Tin Mill Products as sold/shipped. However, individual components of the product have been found to be absorbed by plants from soil.

12(e) Other adverse effects: None Known

Additional Information:

Hazard Category: Not Reported Signal Word: No Signal Word

Hazard Symbol: No Symbol Hazard Statement: No Statement

Section 13 - Disposal Considerations

Disposal: Steel scrap should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled, or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.

Container Cleaning and Disposal: Follow applicable federal, state and local regulations. Observe safe handling precautions. European Waste Catalogue (EWC): 16-01-17 (ferrous metals), 12-01-99 (wastes not otherwise specified), 16-03-04 (off specification batches and unused products), or 15-01-04 (metallic packaging).

Please note this information is for Tin Mill Products in its original form. Any alterations can void this information.

Section 14 - Transport Information

14 (a-g) Transportation Information:

US Department of Transportation (DOT) under 49 CFR 172.101 does not regulate Tin Mill Products as a hazardous material. All federal, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

Shipping Name: Not Applicable (NA)	Packaging Authorizations	Quantity Limitations
Shipping Symbols: NA	a) Exceptions: NA	a) Passenger, Aircraft, or Railcar: NA
Hazard Class: NA	b) Group: NA	b) Cargo Aircraft Only: NA
UN No.: NA	c) Authorization: NA	Vessel Stowage Requirements
Packing Group: NA		a) Vessel Stowage: NA
DOT/ IMO Label: NA		b) Other: NA
Special Provisions (172.102): NA		DOT Reportable Quantities: NA

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate Tin Mill Products as a hazardous material.

Shipping Name: Not Applicable (NA)	Packaging	Portable Tanks & Bulk Containers
Classification Code: NA	a) Packing Instructions: NA	a) Instructions: NA
UN No.: NA	b) Special Packing Provisions: NA	b) Special Provisions: NA
Packing Group: NA	c) Mixed Packing Provisions: NA	
ADR Label: NA		
Special Provisions: NA		
Limited Quantities: NA		

International Air Transport Association (IATA) does not regulate Tin Mill Products as a hazardous material

International An Transport Association	on (iaia) uocs i	iot regulate 1 m ivim 1	Toutes as a mazardot	is material.	
Shipping Name: Not Applicable (NA) Class/Division: NA		Passenger & Cargo Aircraft Limited Quantity (EQ)		Cargo Aircraft Only Pkg Inst: NA	Special Provisions: NA
Hazard Label (s): NA		Pkg Inst: NA	Pkg Inst: NA		
UN No.: NA				Max Net Qty/Pkg:	ERG Code: NA
Packing Group: NA		Max Net Qty/Pkg:	Max Net Qty/Pkg:	NA	
Excepted Quantities (EQ): NA		NA	NA		
Pkg Inst – Packing Instructions Max Net Qty/Pkg – N		Maximum Net Quantity per l	Package	ERG - Emergency Resp	onse Drill Code

Transport Dangerous Goods (TDG) Classification: Tin Mill Products does not have a TDG classification.



SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 15 - Regulatory Information

Regulatory Information: The following listing of regulations relating to an ArcelorMittal product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.

This product and/or its constituents are subject to the following regulations:

OSHA Regulations: Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-2, Z-3): The product, **Tin Mill Products** as a whole is not listed. However, individual components of the product are listed: Refer to Section 8, Exposure Controls and Personal Protection.

EPA Regulations: The product, Tin Mill Products is not listed as a whole. However, individual components of the product are listed:

Components	Regulations
Chromium	CERCLA, CWA, SARA 313, RCRA. SDWA
Nickel	CAA, CERCLA, CWA, SARA 313
Manganese	CAA, SARA 313, SDWA

SARA 311/312 Potential Hazard Categories: Immediate Acute Health Hazard; Delayed Chronic Health Hazard

Section 313 Supplier Notification: The product, Tin Mill Products contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act and 40 CFR part 372:

CAS#	Chemical Name	Percent by Weight
7440-47-3	Chromium	1 max
7439-96-5	Manganese	1.95 max
7440-02-0	Nickel	0.15 max

Regulations Key:

- CAA Clean Air Act (42 USC Sec. 7412; 40 CFR Part 61 [As of: 8/18/06])
- CERCLA Comprehensive Environmental Response, Compensation and Liability Act (42 USC Secs. 9601(14), 9603(a); 40 CFR Sec. 302.4, Table 302.4, Table 302.4 and App. A)
 - CWA Clean Water Act (33 USC Secs. 1311; 1314(b), (c), (e), (g); 136(b), (c); 137(b), (c) [as of 8/2/06])
 - RCRA Resource Conservation Recovery Act (42 USC Sec. 6921; 40 CFR Part 261 App VIII)
 - SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 302 Extremely Hazardous Substances (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65) and Section 313 Toxic Chemicals (42 USC Secs. 11023, 13106; 40 CFR Sec. 372.65 [as of 6/30/05])
 - TSCA Toxic Substance Control Act (15 U.S.C. s/s 2601 et seq. [1976])
 - SDWA Safe Drinking Water Act (42 U.S.C. s/s 300f et seq. [1974])

State Regulations: The product, **Tin Mill Products** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

Pennsylvania Right to Know: Contains regulated material in the following categories:

- Hazardous Substances: Manganese, Nickel, Silicon, Chromium, Chromium Oxide and Tin
- Environmental Hazards: Manganese, Nickel and Chromium
- Special Hazardous Substance: Nickel, Chromium and Chromium Oxide

California Prop. 65: Contains elements known to the State of California to cause cancer or reproductive toxicity. This includes Chromium compounds and Nickel.

New Jersey: Contains regulated material in the following categories:

- Hazardous Substance: Manganese, Nickel, Silicon, Chromium, Chromium Oxide and Tin
- Environmental Hazards: Manganese, Nickel and Chromium
- Special Hazardous Substance: Manganese, Silicon and Chromium

Minnesota: Manganese, Nickel and Chromium

Massachusetts: Manganese, Nickel, Silicon, Chromium, Chromium Oxide and Tin

Other Regulations:

WHMIS Classification (Canadian): The product, Tin Mill Products is not listed as a whole. However individual components are listed.

Ingredients	WHMIS Classification		
Silicon	Flammable solids - Category 2, Combustible dusts		
Manganese	Reproductive toxicity - Category 2, Specific target organ toxicity - repeated exposure - Category 1,		
	Combustible dusts		
Nickel	Skin sensitization – Category 1, Carcinogenicity – Category 2,		
	Specific target organ toxicity – repeated exposure - Category 1		

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Prepared By: ArcelorMittal USA LLC

Original Issue Date: 8/26/2002 Revised Date: 01/01/2016



SDS ID No.: AM USA - 006 Revision: 01/01/2016

Section 16 - Other Information (continued)

Additional Information:

Hazardous Material Identification System (HMIS) Classification

Health Hazard	1
Fire Hazard	0
Physical Hazard	0

HEALTH= 1, Denotes possible chronic hazard if airborne dusts or fumes are generated Irritation or minor reversible injury possible.

FIRE= 0, Materials that will not burn.

PHYSICAL HAZARD= **0**, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

National Fire Protection Association (NFPA)



HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.

FLAMMABILITY = 0, Materials that will not burn.

INSTABILITY = $\mathbf{0}$, Normally stable, even under fire exposure conditions, and are not reactive with water.

ABBREVIATIONS/ACRONYMS:

ACGIH	American Conference of Governmental Industrial Hygienists	NIF	No Information Found
BEIs	Biological Exposure Indices	NIOSH	National Institute for Occupational Safety and Health
CAS	Chemical Abstracts Service	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	ORC	Organization Resources Counselors
CLP	Classification, Labelling and Packaging	OSHA	Occupational Safety and Health Administration
CFR	Code of Federal Regulations	PEL	Permissible Exposure Limit
CNS	Central Nervous System	PNOR	Particulate Not Otherwise Regulated
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract	PNOC	Particulate Not Otherwise Classified
HMIS	Hazardous Materials Identification System	PPE	Personal Protective Equipment
IARC	International Agency for Research on Cancer	ppm	parts per million
LC50	Median Lethal Concentration	RCRA	Resource Conservation and Recovery Act
LD50	Median Lethal Dose	REACH	Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals
LD Lo	Lowest Dose to have killed animals or humans	RTECS	Registry of Toxic Effects of Chemical Substances
LEL	Lower Explosive Limit	SARA	Superfund Amendment and Reauthorization Act
LOEL	Lowest Observed Effect Level	SCBA	Self-contained Breathing Apparatus
LOAEC	Lowest Observable Adverse Effect Concentration	SDS	Safety Data Sheet
μg/m³	microgram per cubic meter of air	STEL	Short-term Exposure Limit
mg/m ³	milligram per cubic meter of air	TLV	Threshold Limit Value
mppcf	million particles per cubic foot	TWA	Time-weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
NFPA	National Fire Protection Association		

Disclaimer: This information is taken from sources or based upon data believed to be reliable. Our objective in sending this information is to help you protect the health and safety of your personnel and to comply with the OSHA Hazard Communication Standard and Title III of the Emergency Planning and Community Right-to-Know Act. ArcelorMittal USA LLC makes no warranty as to the absolute correctness, completeness, or sufficiency of any of the foregoing, or any additional, or other measures that may not be required under particular conditions. THIS ARCELORMITTAL USA LLC SDS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY, OR ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, AND ANY IMPLIED WARRANTIES OTHERWISE ARISING FROM COURSE OF DEALING OR TRADE.

Products covered for Tin Mill Products:

Black Plate	Black Plate as rolled	
Electrolytic Tin Coated Steel	Black Plate Full Finish	
Black Plate Full Hard	Electrolytic Tin Coated Sheet	
Electrolytic Chrome Coated Sheet	Electrolytic Chrome Coated Steel (ECCS and TFS)	

Tin Mill Products

Signal Word: DANGER

Symbols:





HAZARD STATEMENTS:

Causes eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure.

PRECAUTIONARY STATEMENTS

Do not breathe dusts / fume / gas / mist / vapor / spray.

Wear protective gloves / protective clothing / eye protection / face protection.

Contaminated work clothing must not be allowed out of the workplace.

Use only outdoors or in well ventilated areas.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed, concerned or feel unwell: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue Rinsing.

If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and

wash contaminated clothing before reuse. Call a poison center/doctor if you feel unwell.

Dispose of contents in accordance with federal, state and local regulations.

SDS ID No.: AM USA - 006

ArcelorMittal USA LLC 1 South Dearborn Street Chicago, IL 60603-9888

General Information: Phone: 219-787-4901 or email at: msdssupport@arcelormittal.com

CHEMTREC (Day or Night): 1-800-424-9300

Emergency Contact: 1-760-476-3962, (3E Company Code: 333211)

Original Issue Date: 08/26/2002 **Revised:** 01/01/2016