



1. Product and company identification

Product name Rustilo 4135 HF

MSDS # 459509

Historic MSDS #: 09016-AE

Code 459509-US03

Product use Corrosion inhibitor.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Manufacturer Castrol Industrial North America, Inc.
150 W. Warrenville Road
Naperville, IL 60563

Supplier Castrol Industrial North America, Inc.
150 W. Warrenville Road
Naperville, IL 60563
Product Information: 1-800-621-2661

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

2. Hazards identification

Physical state Liquid.

Color Clear. Amber.

Emergency overview CAUTION !

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.
ASPIRATION HAZARD.
HARMFUL OR FATAL IF SWALLOWED.
CAN ENTER LUNGS AND CAUSE DAMAGE.

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Aspiration hazard if swallowed. Can enter lungs and cause damage. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Do not ingest. If ingested, do not induce vomiting. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes May cause eye irritation.

Skin May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Inhalation May cause respiratory tract irritation.

Ingestion Aspiration hazard if swallowed. Can enter lungs and cause damage. Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (section 11)

Product name Rustilo 4135 HF	Product code 459509-US03	Page: 1/6
Version 4.01 Date of issue 02/12/2010.	Format US	Language ENGLISH.
	(US)	(ENGLISH)

3. Composition/information on ingredients

Ingredient name	CAS #	%
Distillates (Petroleum) hydrotreated light	64742-47-8	85 - 90
Refined paraffin wax	8002-74-2	1 - 5

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Skin contact	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

5. Fire-fighting measures

Flash point	Open cup: 112.78°C (235°F) [Cleveland.]
Fire/explosion hazards	In a fire or if heated, a pressure increase will occur and the container may burst.
Extinguishing media	
Suitable	Use an extinguishing agent suitable for the surrounding fire.
Not suitable	Do not use water jet.
Fire-fighting procedures	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)
Protective clothing (fire)	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Product name Rustilo 4135 HF

Product code 459509-US03

Page: 2/6

Version 4.01 **Date of issue** 02/12/2010.

Format US

Language ENGLISH.

(US)

(ENGLISH)

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Occupational exposure limits

Distillates (Petroleum) hydrotreated light

ACGIH TLV (United States). Absorbed through skin.

TWA: 200 mg/m³ 8 hour(s). Issued/Revised: 1/2003

OSHA PEL (United States). Absorbed through skin.

STEL: 10 mg/m³ 15 minute(s). Form: Mist

TWA: 5 mg/m³ 8 hour(s). Form: Mist

Refined paraffin wax

ACGIH TLV (United States).

TWA: 2 mg/m³ 8 hour(s). Issued/Revised: 9/1994 Form: Fume

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Personal protection

Eyes

Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Use adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

9. Physical and chemical properties

Physical state

Liquid.

Color

Clear. Amber.

Odor

Mild.

Flash point

Open cup: 112.78°C (235°F) [Cleveland.]

Specific gravity

0.8 to 0.85

Viscosity

Kinematic: <7 mm²/s (<7 cSt) at 40°C
SUS: 35 to 38 SUS at 37.778°C

Solubility

insoluble in water.

Product name Rustilo 4135 HF

Product code 459509-US03

Page: 3/6

Version 4.01 **Date of issue** 02/12/2010.

Format US

Language ENGLISH.

(US)

(ENGLISH)

10. Stability and reactivity

Stability and reactivity	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Other information

Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

TSCA 12(b) one-time export: dipropylene glycol methyl ether

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Distillates (Petroleum) hydrotreated light; Refined paraffin wax

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Rustilo 4135 HF: Immediate (acute) health hazard

Product name Rustilo 4135 HF

Product code 459509-US03

Page: 4/6

Version 4.01 **Date of issue** 02/12/2010.

Format US

Language ENGLISH.

(US)

(ENGLISH)

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):

CERCLA: Hazardous substances.: No products were found.

State regulations

Massachusetts Substances

The following components are listed: PARAFFIN WAX FUME

New Jersey Hazardous Substances

The following components are listed: PARAFFIN WAX; PARAFFIN WAXES and HYDROCARBON WAXES

Pennsylvania RTK Hazardous Substances

The following components are listed: PARAFFIN WAXES AND HYDROCARBON WAXES

California Prop. 65

California Prop 65: No products were found

Inventories

Canada inventory

All components are listed or exempted.

Europe inventory

All components are listed or exempted.

Australia inventory (AICS)

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (ENCS)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

16. Other information

Label requirements

CAUTION !

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.
ASPIRATION HAZARD.
HARMFUL OR FATAL IF SWALLOWED.
CAN ENTER LUNGS AND CAUSE DAMAGE.

HMIS® Rating :

Health 1
Flammability 1
Physical Hazard 0
Personal protection B

National Fire Protection Association (U.S.A.)



History

Date of issue

02/12/2010.

Date of previous issue

12/13/2005.

Prepared by

Product Stewardship

Notice to reader

Product name Rustilo 4135 HF

Product code 459509-US03

Page: 5/6

Version 4.01 **Date of issue** 02/12/2010.

Format US
(US)

Language ENGLISH.
(ENGLISH)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name Rustilo 4135 HF

Product code 459509-US03

Page: 6/6

Version 4.01 **Date of issue** 02/12/2010.

Format US

Language ENGLISH.

(US)

(ENGLISH)