

Issuing Date 09-Jun-2015

Revision Date 09-Jun-2015

Revision Number 0

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

### GHS product identifier

**Product Name** Chromium Alloyed Stainless Steel grades

### Other means of identification

**Synonyms** 405, 409, 410, 416, 420, 429, 430, 434, 439, 441, and 444. This includes all listed grades with letter prefixes and suffixes as well as PRODEC® suffix.

### Recommended use of the chemical and restrictions on use

**Recommended Use** Solid stainless steel products, various forms, and uses

**Uses advised against** No information available

### Supplier's details

Outokumpu Stainless Plate, LLC 549 W. St. Rd. 38 New Castle, IN 47362 Tel: 1-800-349-0023; 1-765-529-0120	Outokumpu Stainless Pipe, LLC 241 West Clarke Street Wildwood, FL 34785 Tel: 1-800-731-7473; 1-352-748-1313	Outokumpu Mexinox S.A de C.V Av. Industrias No.4100, Zona Industrial 1a. Sección, 78395, San Luis Potosí, México Tel: +52+444+826-5100
Outokumpu Stainless Bar, LLC 3043 Crenshaw Parkway Richburg, SC 29729 Tel: 1-888-458-4600; 1-803-789-5383	Outokumpu Stainless USA, LLC One ThyssenKrupp Dr. P.O. Box 13000 Calvert, AL 36513-13000 Tel: 1-251-829-3600	Additional Information Contact: Tel: 1-800-349-0023 Web site: <a href="http://www.outokumpu.com">www.outokumpu.com</a>

### 1.4. Emergency Telephone Number

**Emergency Number : 1-765-529-0120**

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200). Solid metallic products are generally classified as "articles" and do not constitute hazardous materials in solid form. However, downstream use of the article could result in some hazardous elements contained in these products to be emitted under certain processing conditions such as but not limited to: burning, melting, cutting, sawing, brazing, grinding, machining, milling, and welding.

### GHS Label elements, including precautionary statements

No labeling elements applicable.

### Hazard Not Otherwise Classified (HNOC)

Not applicable

### Other information

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Synonyms**

405, 409, 410, 416, 420, 429, 430, 434, 439, 441, and 444. This includes all listed grades with letter prefixes and suffixes as well as PRODEC® suffix.

Chemical Name	CAS-No	Weight %	Trade secret
Iron	7439-89-6	Balance	*
Chromium	7440-47-3	10.5-19.5	*
Molybdenum	7439-98-7	0-2.5	*
Manganese	7439-96-5	0-1.25	*
Silicon	7440-21-3	0-1.0	*
Nickel	7440-02-0	0-0.75	*
Copper	7440-50-8	0-0.6	*
Cobalt	7440-48-4	0-0.6	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of necessary first-aid measures****General Advice**

In its solid form stainless steel does not present an inhalation, absorption, or ingestion hazard. Grinding, polishing, abrasive blasting, hot rolling, hot forging, thermal cutting, or welding may produce stainless steel dust or fumes containing complex or mixed oxides (spinels) of its components. Metal dust particles may cause eye, skin and/or respiratory system irritation. The below information is for these instances.

**Eye Contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a physician.

**Inhalation**

Move to fresh air. If breathing is difficult, give oxygen. Consult a physician.

**Ingestion**

Not an expected route of exposure. If swallowed: Get medical attention.

**Most important symptoms/effects, acute and delayed****Most Important Symptoms/Effects**

During processing: Coughing and/ or wheezing. Difficulty in breathing. Irritation. May cause allergic skin reaction.

**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician**

May cause sensitization by inhalation and skin contact. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** None

### Specific Hazards Arising from the Chemical

Avoid dust formation. Dust can form an explosive mixture in air. May cause sensitization by inhalation and skin contact.

### Explosion Data

<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Avoid dust formation. Avoid inhalation of dust. Ensure adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment. Use personal protective equipment. Avoid contact with skin, eyes and clothing.
-----------------------------	--

### Environmental Precautions

<b>Environmental Precautions</b>	Not applicable to steel in solid state. Follow applicable federal, state and local regulations
----------------------------------	--

### Methods and materials for containment and cleaning up

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so. Cover dust spill with plastic sheet or tarp to minimize spreading.
<b>Methods for Cleaning Up</b>	Take up mechanically and collect in suitable container for disposal. Avoid dust formation. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

<b>Handling</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation. Avoid breathing dust. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not eat, drink or smoke when using this product.
-----------------	--

### Conditions for safe storage, including any incompatibilities

<b>Storage</b>	Store in accordance with local regulations.
<b>Incompatible Products</b>	May react in contact with strong acids to release gaseous acid decomposition products, e.g. hydrogen, oxides of nitrogen. Use of strong oxidizers (high pH) on stainless steel may cause Cr(VI) compounds to form at ambient temperatures. Decomposition: Fumes generated during welding, brazing, or thermal cutting may contain: chromium compounds, including hexavalent chromium Cr(VI); nickel; manganese; iron; molybdenum; and silicon compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

There are no occupational exposure limits for stainless steels. Occupational exposure limits apply to some components resulting from grinding, polishing, abrasive blasting, hot rolling, hot forging, thermal cutting, or welding which may produce stainless steel dust or fumes.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Molybdenum 7439-98-7	TWA: 10 mg/m <sup>3</sup> inhalable fraction TWA: 3 mg/m <sup>3</sup> respirable fraction	(vacated) TWA: 10 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup>
Manganese 7439-96-5	TWA: 0.2 mg/m <sup>3</sup>	(vacated) TWA: 1 mg/m <sup>3</sup> fume (vacated) STEL: 3 mg/m <sup>3</sup> fume (vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> fume	IDLH: 500 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup> fume STEL: 3 mg/m <sup>3</sup>
Silicon 7440-21-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Nickel 7440-02-0	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Cobalt 7440-48-4	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> dust and fume (vacated) TWA: 0.05 mg/m <sup>3</sup> dust and fume	IDLH: 20 mg/m <sup>3</sup> dust and fume TWA: 0.05 mg/m <sup>3</sup> dust and fume

### Appropriate engineering controls

#### Engineering Measures

Ensure adequate ventilation, especially in confined area (i.e. showers, eyewash stations, etc.).

### Individual protection measures, such as personal protective equipment

#### Eye/Face Protection

When processing the metal alloy wear: Tightly fitting safety goggles.

#### Skin and Body Protection

When processing the metal alloy: Wear protective gloves/clothing.

#### Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical State	Solid	Appearance	Varying from dull very light grey, to shiny metallic light grey to bright mirror-finish
Odor	Odorless	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	1370-1520 °C / 2498-2768 °F	None known
Boiling Point/Boiling Range	No data available	None known
Flash Point	No data available	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air upper flammability limit	No data available	None known

<b>lower flammability limit</b>	No data available	
<b>Vapor Pressure</b>	No data available	None known
<b>Vapor Density</b>	No data available	None known
<b>Relative Density</b>	No data available	None known
<b>Specific Gravity</b>	No data available.	None known
<b>Water Solubility</b>	No data available	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition Temperature</b>	No data available	None known
<b>Decomposition Temperature</b>	No data available	None known
<b>Viscosity</b>	No data available	None known
<b>Flammable Properties</b>	Not flammable	
<b>Explosive Properties</b>	No data available	
<b>Oxidizing Properties</b>	No data available	

**Other information**

**VOC Content (%)** No data available

**10. STABILITY AND REACTIVITY****Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Dust formation.

**Incompatible materials**

May react in contact with strong acids to release gaseous acid decomposition products, e.g. hydrogen, oxides of nitrogen. Use of strong oxidizers (high pH) on stainless steel may cause Cr(VI) compounds to form at ambient temperatures. Decomposition: Fumes generated during welding, brazing, or thermal cutting may contain: chromium compounds, including hexavalent chromium Cr(VI); nickel; manganese; iron; molybdenum; and silicon compounds.

**Hazardous decomposition products**

None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

In its solid form stainless steel does not present an inhalation, absorption, or ingestion hazard. Grinding, polishing, abrasive blasting, hot rolling, hot forging, thermal cutting, or welding may produce stainless steel dust or fumes containing complex or mixed oxides (spinels) of its components. Metal dust particles may cause eye, skin and/or respiratory system irritation. The below information is for these instances.

**Inhalation** - May cause irritation of respiratory tract. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Eye Contact**  
**Skin Contact** - Contact with dust can cause mechanical irritation or drying of the skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

**Ingestion** - May cause irritation

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Iron	= 984 mg/kg ( Rat )	-	-
Manganese	= 9 g/kg ( Rat )	-	-
Silicon	= 3160 mg/kg ( Rat )	-	-
Nickel	> 9000 mg/kg ( Rat )	-	-
Cobalt	= 6170 mg/kg ( Rat )	-	> 10 mg/L ( Rat ) 1 h

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** - No information available.

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Sensitization** - Dust generated during processing may cause sensitization by inhalation and skin contact  
**Mutagenic Effects** - No information available.  
**Carcinogenicity** - The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Chromium		Group 3		
Nickel		Group 2B Group 1	Reasonably Anticipated	X
Cobalt	A3	Group 2A Group 2B		X

**Reproductive Toxicity** - No information available.  
**STOT - single exposure** - No information available.  
**STOT - repeated exposure** - No information available.  
**Chronic Toxicity** - Elevated temperature processing such as welding and plasma arc cutting may release hazardous fumes. Overexposure to metal fumes may cause pulmonary edema (fluid in the lungs) and methemoglobinemia. May also cause pulmonary fibrosis and lung cancer. Chronic exposure to manganese may cause impairment to the central nervous system including sluggishness, sleepiness, muscle weakness, loss of facial muscle control, edema, emotional disturbances, spastic gait, and falling.

**Target Organ Effects** - Respiratory system. Skin.  
**Aspiration Hazard** - No information available.

**Numerical measures of toxicity - Product**

The following values are calculated based on chapter 3.1 of the GHS document:

**LD50 Oral** - 830 mg/kg; Acute toxicity estimate

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron	-	LC50 96 h: = 0.56 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 13.6 mg/L static (Morone saxatilis)	-	-

Nickel	EC50 96 h: 0.174 - 0.311 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 0.18 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 1.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 10.4 mg/L static (Cyprinus carpio) LC50 96 h: > 100 mg/L (Brachydanio rerio)	-	EC50 48 h: = 1 mg/L Static (Daphnia magna) EC50 48 h: > 100 mg/L (Daphnia magna)
Cobalt	-	LC50 96 h: > 100 mg/L static (Brachydanio rerio)	-	-
Copper	EC50 96 h: 0.031 - 0.054 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 0.0426 - 0.0535 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.0068 - 0.0156 mg/L (Pimephales promelas) LC50 96 h: < 0.3 mg/L static (Pimephales promelas) LC50 96 h: = 0.052 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.112 mg/L flow-through (Poecilia reticulata) LC50 96 h: = 0.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.8 mg/L static (Cyprinus carpio) LC50 96 h: = 1.25 mg/L static (Lepomis macrochirus)	-	EC50 48 h: = 0.03 mg/L Static (Daphnia magna)

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available.

**Other Adverse Effects**

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Methods**

Recover or recycle if possible. Dispose of in accordance with federal, state, and local regulations

**Contaminated Packaging**

Dispose of in accordance with federal, state, and local regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Chromium - 7440-47-3		Included in waste streams: F032, F034, F035, F037, F038, F039	5.0 mg/L regulatory level	
Nickel - 7440-02-0	(hazardous constituent - no waste number)	Included in waste streams: F006, F039		
Chemical Name		California Hazardous Waste		
Chromium		Toxic Corrosive Ignitable		
Molybdenum		Ignitable powder		
Manganese		Ignitable powder		
Nickel		Toxic powder Ignitable powder		
Copper		Toxic		
Cobalt		Toxic powder Ignitable powder		

**14. TRANSPORT INFORMATION**

**DOT**

Not regulated

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

TSCA	Complies
DSL	Complies

**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Chromium	7440-47-3	10.5-19.5	1.0
Manganese	7439-96-5	0-1.25	1.0
Nickel	7440-02-0	0-0.75	0.1
Cobalt	7440-48-4	0-0.6	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Nickel		X	X	
Copper		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Chromium			RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Nickel	7440-02-0	Carcinogen
Cobalt	7440-48-4	Carcinogen



**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Chromium		X			X
Molybdenum	X	X	X		X
Manganese	X	X	X	X	X
Silicon	X	X	X		X
Titanium	X				
Nickel	X	X	X	X	X
Cobalt	X	X	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION				
<b>NFPA</b>	Health Hazard 0	Flammability 0	Instability 0	Physical and Chemical Hazards -
<b>HMS</b>	Health Hazard 0	Flammability 0	Physical Hazard 0	Personal Protection X

Prepared By Product Stewardship  
 23 British American Blvd.  
 Latham, NY 12110  
 1-800-572-6501

Issuing Date 09-Jun-2015  
 Revision Date 09-Jun-2015  
 Revision Note Initial Release.

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**