

Impax™ — Performance Self-Drill

12-14 Impax and 1/4-14 Impax lap self-drill

For metal to metal


- Precision cold forged assuring superior point strength and the fastest drilling time performance through high strength steel and nested purlins.
- Ultimate performance in light, medium and heavy gage applications.

- Designed and engineered to have low driving and thread engagement torque and provide maximum clamp load.
- Corrosion resistant coating system.

Application

12-14 Impax
Metal to metal

Drilling capacity: .035 – .210"
Thickness is based on normal, single thickness purlin/girt or multiple material thickness combined for total.
Min projection: 3/16" of threads below substrate



5/16" AF Hex Washer Head
Thread Major Dia: .215 – .209
Thread Minor Dia: .164 – .157

Strength (lbs ult.):

Tensile: 2900
Torsional: 92 in-lbs
Shear: 2050

Pull-out (lbs ult.):



12 ga (.109): 1524
14 ga (.075): 901
16 ga (.060): 665

Pull-over with Bond Seal (lbs ult.):

22 ga (.030): 1249
24 ga (.024): 1056
26 ga (.018): 654

1/4-14 Impax Lap
Panel to panel side lap

Drilling capacity: .030 – .095"
Some applications may require attaching light gage (24 – 26 ga) to sub-structural member.
Composite thickness should not exceed .095".



5/16" AF Hex Washer Head
Thread Major Dia: .246 – .240
Thread Minor Dia: .192 – .185

Strength (lbs ult.):

Tensile: 3800
Torsional: 150 in-lbs
Shear: 2850

Pull-out (lbs ult.):

22 ga (.030): 379
24 ga (.024): 304
26 ga (.018): 204

Notes

Dimensions are nominal inches unless noted. Self-drill pull-out values (pounds ultimate) are based on 57,000 psi hot rolled steel material. Lap self-drill pull-out values are based on 40,000 psi AZ55 Galvalume steel sheet material. Ultimate values listed are the result of laboratory testing (5083.14). The specific job conditions should be considered and appropriate safety factors applied when specifying the proper fasteners. #12 fasteners 1" and longer have special long pilot lengths to accommodate nested purlins.

Selection

Description	Available Lengths (L)	Example Code				
		Type	Diameter	Length	Head Style	Washer
#12-14 Impax SD3 with Bond Seal	3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	SD3-	#12x	1-1/2-	HW5/16-	GB19/32
#12-14 Impax SD3 No Washer	3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	SD3-	#12x	L-	HW5/16-	—
1/4-14 Impax Lap with Bond Seal	7/8"	SDL-	#14x	L-	HW5/16-	GB9/16
1/4-14 Impax Lap No Washer	7/8"	SDL-	#14x	L-	HW5/16-	—

Installation

Tools: 0 – 2000 rpm screw gun equipped with depth sensing nose piece.

Options

